

MODEL P702-59

High Speed Strapping Machine



Features

Up to 65 Straps per Minute

5mm, 6mm or 9mm Polypropylene Strapping

High Performance DC Brushless Motor Technology

Precision Electronic Tension

Loop Ejector

Coil End Strap Ejector

Anti Jam Technology

Compact Frame with Internal Strapping Dispenser

Auto Strap Loading at Waist Height

Foot Bar, Photo Eye and Panel Switch are All Standard on Every Machine

Track Design Insures Precision Strap Placement

Roller Table Tops Standard on 33" Wide Sizes and Up



Model P-702-59

Automatic Strapping Machine

Product Features

The P702 is a world class high speed automatic strapping machine. It features several creative designs that make it the most operator friendly machine it its class.

The operator control panel is hinged to allow access from either side of the machine. The Smart LCD display offers enhanced diagnostics and the ability to make adjustments.

The compact frame of the P702-59 features an inside mount strap dispenser that hinges up for auto strap loading at waist height. The new quick release dispenser flange lock knob makes coil changes faster.

All P702 series machines have a hinged open top plate for easy access to the strapping head. They also feature quick release feed guides for immediate access to the strap feed system with the need for tools.

Available Options

- Stainless Steel Frame
- Press Assembly
- Foot Switch
- High Tension for 9mm Model

Standard Arch Sizes

| H\\ | N | 21" | 25" | 33" | 41" | 49" | 64" |
|-----|-----|-----|-----|-----|-----|-----|-----|
| 15 | -11 | Х | | Х | | | |
| 19 |)" | | Х | Х | | | Х |
| 23 |)11 | | | Х | | | |
| 31 | 11 | | | Х | Χ | Х | |
| 39 |)" | | | | Х | Х | |

Specifications

| Min. Bundle Dimensions | 2.5" W x 1" H |
|------------------------|---|
| Max. Bundle Dimensions | Arch Width x Arch Height |
| Table Height | 32.25" to 36.25" |
| Tensioning Range | 2 to 70 lbs |
| Strapping Speed | Up to 65 cycles per minute |
| Strapping Used | 5mm, 6mm or 9mm Embossed |
| Strapping Oseu | Jillill, Ollilli Ol Jillill Ellibossed |
| Strapping Osed | or Smooth Strapping |
| Power Supply | |
| 11 3 | or Smooth Strapping |
| Power Supply | or Smooth Strapping 110V (220, 230) Single Phase |

Distributed By:



Photo Eye



Internal Dispenser



Hinged Open Tops



Adjustable Height